## **COSTAR** VIDEO SYSTEMS

## **CMR-IPC25IR**

### **HD Network Camera**



Description:	Features:
The Costar IPC25IR Flat Dome IP network camera is a rugged high definition 1080p camera that is perfect for mobile applications. The metal enclosure is water/dust proof with an IP65 rating. It has a built-in microphone and provides a full 1920x1080 resolution at 30fps. With multiple lens options, you will capture the field of view needed in any fixed mobile environ- ment. Eight (8) high-output infrared LEDs with an IR cut filter provide high resolution images in all light conditions. Power over Ethernet (PoE) or our proprietary 6-pin Power over Network (PoN) provide 12v to 48vdc power used in most vehicles.	<ul> <li>1920x1080@30fps Resolution</li> <li>Built-in power loss protection</li> <li>Compact size - light weight</li> <li>Day/Night(ICR), Super Wide Dynamic Range, Auto Wide Light Compensation</li> <li>IP65 water proof and dust proof</li> <li>Separate audio channel</li> <li>Available lens: 2.6mm, 2.8mm &amp; 4mm</li> <li>POE(DC 12V)</li> <li>Anti-vibration, vandal resistant</li> </ul>



# **CMR-IPC25IR Specifications**

Model	Lens (mm) 2.6mm, 2.8mm, 4mm		Resolution 1920x1080
CMR-IPC25IR			
· · · · · · · · · · · · · · · · · · ·			·
Power		General Info	ormation
Power Consumption: <2w (Day) <3.5w	light)	Temperature	: -40°F - 158°F
Power Supply: POE(DC12V)		Humidity: 0%	
Camera Parameters			Class: IP66 wo audio / IP65 with audio
Sensor: 1/2.9" CMOS		Dimensions	;
<b>Resolution:</b> 1920(H) x 1080(V)		L x W x H: 10	1.5mm x 96mm x 52.6mm
Signal System: 50/60 Hz			
Minimum Illumination: 0.1Lux (Color Illu			
Electronic Shutter: 1/30 Second -1/100	00 Second	61	
Day/Night:			
Wide Dynamic Range: 80db			96
Black-light Compensation: Support			
<b>S/N:</b> ≥48db			H H H
Wide Dynamic Range: ≥80db			2.6 mm
<b>IR:</b> <12-20m			
Optical Lens			
Port: M12		101.5 m	nm I
Aperture: Fixed aperture F1.8			
Lens: 2.6mm, 2.8mm, 4mm			
Audio/Video Encode			
Video Compression: H.264			
Compression Output Rate: 512Kbps-8	Mbps		
Image Resolution: Main Stream:1080p			
Network Sub Stream:VGA,WD1,D1,QV			
Net transmission str	eam:Dynamic		
CBR/VBR: Support			
Image			
Maximum Image: 1920x1080			
Frame: 30FPS			
Image Setting: Chroma, contrast, satura	ation & sharpness		
Network Protocol: HTTP, TCP, RTSP,			
ONVIF: Support			
Client Terminal Preview: Built-in WEB	server:		
Support IE br			
Storage: Client Terminal/ MDVR			
specification are subject to change without notice.			



101 Wrangler, Suite 201 • Coppell, Texas 75019 • Phone: 469-635-6800 x1142 • Fax: 469-635-6822

#### Rev. 11/07/19 v.1.0

### www.costarmobilevideo.com